

Specification Text

Automatic Sliding Door

Dimensions

Overall width	 mm
Overall height	 mm
Passage width	 mm (800 – 3800 mm)
Passage height	 mm

TORMAX iMotion® 2202 Sliding Door Drive

Automatic sliding door drive for single or double-leaf sliding doors, standard or telescopic.

- Max. door leaf weight 1 x 130 kg, 2 x 120 kg, telescope 4 x 80 kg, 2 x 80 kg.
- Cross section header profile (HxD) 100x142 mm, telescope 100x204 mm
- In compliance with current European standards

(_) Electromechanical sliding door drive with wear-free synchronous motor technology and processor control. Mains supply 115 VAC/60 Hz or 230 VAC/50 Hz

- Protective system IP22, ambient temperature –20 °C to +50 °C.
RoHS conformity (EC directive 2002/95/EG).
- Easily replaceable noise-damped guide rail.
- Integrated cable duct and integrated concealed sealing brushes.
- Mounting method: Lintel mounting, wall mounting, ceiling mounting.
- Tested by TÜV and certified according to EN IEC 60335, DIN 18650: 2010, EN ISO 13849: 2008 Performance level „d“.
- **Control System**
Automatic detection of system-specific data for optimal motion control, permanent operating diagnosis.
- Electronic obstacle recognition in closing and opening directions, adjustable reversing sensibility
- Automatic speed limit, including in the event of power failure and in manual mode.
- Emergency opening for autonomous door opening in the event of power failure in the unlocked state.
- 32 Bit/30 MHz processor for high performance.
- Interfaces: LIN BUS, CAN BUS, RS 232
- Fault recognition, display and log.
- Air-lock-function

- User interface with fault diagnosis and code lock. Selectable operating modes: OFF, AUTOMATIC 1, AUTOMATIC 2, EXIT , OPEN and MANUAL.
Freewheeling function and reset selectable on operating unit.
- 8 inputs (4 testable safety devices)
- 3 programmable outputs (optional feedback signals for different door statuses, such as: Closed, Open, Fault, Lock status, Light pulse, Gong pulse).
- Modular extendable by max. 2 I/O-modules (4 in-/outputs each)
- Integration in higher-level system possible, e.g. a building management system, optionally via potential-free contacts or a bus system

Door leaves

- (_) Sliding leaf
- (_) Stationary lateral components
- (_) Stationary fanlights, (_) -part

Profiles

- (_) TORMAX Profile System LR 12
 - Single-sheet glazing
 - Glazing thickness 6 – 12 mm
 - Type of glazing: wet, single-sheet/compound toughened safety glass
 - Facial width 22 mm, base height 80 mm, profile depth 20 mm
- (_) TORMAX Profile System LR 22B
 - Single-sheet and insulating glazing
 - Glass thickness dry 8.5 – 10 mm, 21.5 – 23 mm, wet 6 – 28 mm
 - Facial width 30 mm, base height 78 mm, profile depth 34 mm
- (_) TORMAX Profile System LR 32THERM
 - Insulating glazing
 - Glazing thickness max. 32mm,
 - Facial width 35mm, base height 85mm, profile depth 40mm
- (_) Make.....

Floor guide

- (_) Continuous floor guide in CNS, including glider in the sliding leaf
- (_) Continuous floor guide in aluminium anodised E6/EV1 incl. gliding piece in sliding leaf

Colour of visible profiles

Elox anodising colour

Powder coating RAL

.....

Glazing

- (_) Single-sheet safety glass 10 mm, heat soak tested
 - (_) Compound safety glass 10 mm, with 0.78 mm film
 - (_) Insulating glass comprising 2 x 5 mm single-sheet safety glass, heat soak tested, 22 mm
- Overall thickness, U_g 1.3 W/m²K

- (_) Insulating glass comprising 2 x 6 mm compound safety glass, film 0.78 mm, 22 mm
Overall thickness, Ug 1.3 W/m²K
- (_) Double insulating glass comprising 2 x VSG, overall thickness 31.1mm, Ug
1.0W/(m²/K)
- (_) Triple insulating glass comprising 3 x ESG, overall thickness 32mm, Ug 0.8W/(m²/K)
- (_) Make.....

Sensors

Activation

- (_) Radar
- (_) Active infrared
- (_) Passive infrared
- (_) Contact-free hand switch
- (_) Manual hand switch

Safety facility

- (_) Dynamic safety (with/without testing)
- (_) Static safety (with/without testing)
- (_) Combined detector/alarm (radar and 3D protective light curtain AIR) with testing

Safety assessment conforming to DIN 18650 recommended. A declaration of conformity of the door system is mandatory in the area of validity of the machine guidelines 98/37/EG.

Accessories

- (_) User interface with 6 operating modes and fault display, 45 x 45 mm suitable for
Legrand system
- (_) 3-position operating mode switch mounted in plastic case
- (_) Monitored battery module for emergency power supply
- (_) Electromechanical lock (bistable lock) with feedback, acting only on hardened holding
bolts of the leaf, not acting on the toothed belt or deflection pulley
- (_) Emergency opening including burglary protected emergency unlocking
- (_) Emergency opening monitoring facility
- (_) Emergency OFF switch, optionally surface-mounted or flush-mounted,
with glass cover and frame
- (_) Integration in system network with contacts communication
- (_) Integration in system network with bus communication